Safety data-sheet (91/155 EEC) Printed 19.10.2002

Revision 05.09.2002 (GB) Version 1.2

Lithofin MN-Slate-Oil

### 1. Identification of the substance/preparation

Name of product Lithofin MN-Slate-Oil

Manufacturer/distributor CASDRON Enterprises Ltd.

Wood End, Prospect Road, Alresford Hampshire SO24 9QF

Phone 0 19 62 73 21 26, Fax 0 19 62 73 53 73

Advice Technical Department

Phone 0 19 62 73 21 26

Recommended intended purpose(s)

Care Product

# 2. Composition/information on ingredients

#### **Chemical characterization**

Solvent based wax

**Hazardous ingredients** 

CAS-No. EC-No. Name [% weight] Classification

064742-82-1 265-185-4 Naphtha (petroleum), hydrodesulfurized heavy > 25 Carc.Cat.2 R45; Xn R65

Additional advice

Benzene < 0.1 %

# 3. Special hazards information for man and environment

# R-phrases

10 Flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed. 67 Vapours may cause drowsiness and dizziness.

## 4. First aid measures

## **General information**

Remove contaminated soaked clothing immediately.

## In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

## In case of skin contact

In case of contact with skin wash off immediately with soap and water.

## In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

### In case of ingestion

Do not induce vomitting.

If swallowed by mistake drink plenty of water and seek medical treatment.

## 5. Fire-fighting measures

## Suitable extinguishing material

Foam

Dry powder

Carbon dioxide

sand

## Extinguishing material that may not be used for safety reasons

Full water jet

# Special exposure hazards arising from the substance, combustible products or resulting gases

In case of fire formation of dangerous gases possible.

Printed 19.10.2002

Revision 05.09.2002 (GB) Version 1.2

Lithofin MN-Slate-Oil

#### 6. Accidental release measures

### **Personal precautions**

Ensure adequate ventilation. Use personal protective clothing.

#### **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

## Methods for cleaning up/taking up

Take up with absorbent material (e.g. sand, sawdust, general-purpose binder).

## 7. Handling and storage

# Advice on safe handling

Use only in thoroughly ventilated areas.

Use solvent-resistant equipment.

Take the usual precautions when handling with chemicals.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Take precautionary measures against static discharges.

## Further information on storage conditions

Keep container dry, tightly closed and store at cool and aired place.

### 8. Exposure controls / personal protection

CAS-No.	th occupational exposure limits to be monitored Name	Code	[mg/m³]	[ml/m³]	Remark
	naphtha (petroleum), arom. 1-25 %	MAK	500	100	31, TRGS 901- 72

### **Respiratory protection**

Breathing apparatus in the event of high concentrations.

Short term: filter apparatus, filter A

#### **Hand protection**

chemical-resistant gloves

#### Eye protection

safety goggles

#### **General protective measures**

Avoid contact with eyes and skin

## Hygiene measures

At work do not eat, drink and smoke.

## 9. Physical and chemical properties

Form	Colour	Odour
liquid	colourless, clear	aromatic

### Data relevant for safety

	Value	Temperature	at	Method	Remark
pH value in delivery state	not applicable				
starts to boil	> 130 °C				
Flash point	> 23 °C				
Lower explosion limit	ca. 0,6 Vol-%				

Upper explosion limit ca. 8 Vol-%

Printed 19.10.2002

Revision 05.09.2002 (GB) Version 1.2

Lithofin MN-Slate-Oil

Value	Temperature	at	Method	Remark
ca. 0,8 g/cm3				
				more or less insoluble
< 30 s			ISO 2431/3 mm	
	ca. 0,8 g/cm3	ca. 0,8 g/cm3	ca. 0,8 g/cm3	ca. 0,8 g/cm3

# 10. Stability and reactivity

#### Conditions to avoid

No hazardous reactions known.

# 11. Toxicological information

## Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
LD 50 acute oral	not determined			
LD 50 acute dermal	not determined			
LC 50 acute inhalation	not determined			

# 12. Ecological information

Data on elimination (persistence and degradability)

	Elimination rate	Method of analysis	Method	Validation
Physico-chemical degradability	not determined			
Biological degradability	not determined			

## 13. Disposal considerations

Waste code No. Name of waste

07 02 04\* other organic solvents, washing liquids and mother liquors

## Recommendations for the product

In accordance with regulations for special waste, must be taken to a special waste disposal.

#### Recommendations for packaging

Totally emptied packaging may be taken for recycling.

## 14. Transport information

Land and inland navigation transport (ADR/RID/GGVS/GGVE/ADNR)

**Identification** Flammable liquid, n.o.s. (White spirit)

UN-No. 1993
Class 3
PG III
Hazard No. 30

Safety data-sheet (91/155 EEC) Printed 19.10.2002

Revision 05.09.2002 (GB) Version 1.2

Lithofin MN-Slate-Oil

Marine transport IMDG/GGV See

**Proper shipping name** Flammable liquid, n.o.s., (White spirit)

UN-No. 1993
Class 3
PG Ⅲ
Marine pollutant No
EmS-No. 3-07

Air transport ICAO/IATA

**Proper shipping name** Flammable liquid, n.o.s. (White Spirit)

UN/ID-No. 1993 Class 3 PG III

## 15. Regulatory information

#### Remarks for classification

The product is classified and labelled in accordance with EC directives.

## Classification

Xn Harmful

N Dangerous for the environment

R-phrases

10 Flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed. 67 Vapours may cause drowsiness and dizziness.

S-phrases

2 Keep out of the reach of children.

23.3 Do not breathe vapour.24 Avoid contact with skin.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

### Hazardous ingredients for labeling

Naphtha (petroleum), hydrodesulfurized heavy

# **National regulations**

Classification according to VbF/ All

remarks

Water hazard class 2 VwVwS (17. 05. 1999)

## 16. Other information

#### **Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the poperties of the product.

## Wording of the R-phrases specified in chapter 2 (not the classification of the formulation!)

R 45 May cause cancer.

R 65 Harmful: may cause lung damage if swallowed.